

Technical data													
Type TITANIUM		14			18			20			25		
Drive		CD	E	CD-E	CD	E	CD-E	CD	E	CD-E	CD	E	CD-E
Splitting force	kN/t	130/13			160/16			200/20			250/25		
Max. splitting height	mm	1090	1090	1090	1090	1090	1090	1090	1090	1090	1150	1150	1150
Cylinder stroke	mm	1050	1050	1050	1050	1050	1050	1050	1050	1050	1050	1050	1050
Max. diameter of the workpiece	mm	400	400	400	600	600	600	700	700	700	800	800	800
Height in transport position	mm	1720	1720	1720	1720	1720	1720	1720	1720	1720	1720	1720	1720
Height in working position	mm	2435	2435	2435	2650	2650	2650	2650	2650	2650	2650	2650	2650
Weight	kg	271	280	295	390	411	426	435	456	471	485	516	531
Oil quantity	L	20	20	20	35	35	35	40	40	40	45	45	45
Recommended tractor power	kW/HP	21/29	/	21/29	25/34	/	25/34	27/37	/	27/37	30/41	/	30/41
Electric motor	kW (V)	/	4 kW (380 V)	4 kW (380 V)	/	5,5 kW (380 V)	5,5 kW (380 V)	/	5,5 kW (380 V)	5,5 kW (380 V)	/	7,5 kW (380 V)	7,5 kW (380 V)
Splitting table		■	■	■	■	■	■	■	■	■	■	■	■
Splitting cross		□	□	□	□	□	□	□	□	□	□	□	□
Hander		□	□	□	■	■	■	■	■	■	■	■	■
Autospeed (AS)		x	x	x	x	x	x	x	x	x	■	■	■

■ Serial, □ Option, x not possible, CD-Tractor drive, E-Electric motor, CD-E - Combination, AS-Automatic speed regulation